

PosiTest[®] DFT

Coating Thickness Gage

Ideal for...

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers

2 Models...

Ferrous for STEEL

Combo for ALL METALS



simply
measures

DeFelsko[®]
The Measure of Quality

PosiTest[®] DFT

Coating Thickness Gage

Actual Size

Two Models

- **PosiTest DFT Ferrous**
measures non-magnetic coatings on steel.
- **PosiTest DFT Combo**
measures both non-magnetic coatings on steel AND non-conductive coatings on aluminum, brass, etc. **Automatically** recognizes the substrate and takes a measurement.



Features

- Fast, repeatable measurements
- Ready to measure—no calibration required for most applications
- ZERO feature for rough or curved surfaces
- 1 Point Calibration Adjustment feature for adjusting to a known thickness
- Displays the moving average for up to the last 10 measurements
- Handy RESET feature when no zero reference is available
- Strong, wear-resistant, ruby-tipped probe
- FLIP Display enables right-side-up viewing
- V-groove in probe for positioning on cylindrical parts
- Basic instructions on the back of each gage
- Audible and visible measurement indication
- MILS/Microns switchable
- Built-in wrist strap for added convenience and safety
- Two year warranty on gage body AND probe

Specifications

Measurement Range	0 – 40 mils	0 – 1000 μ m
Accuracy	$\pm(0.1 \text{ mils} + 3\%)$	$\pm(2\mu\text{m} + 3\%)$
Size	4 x 1.5 x 0.9 in.	100 x 38 x 23 mm
Weight	2.5 oz.	70 g

Gage Comes Complete with built-in probe, wrist strap, precision plastic shims, hard shell storage case, AAA alkaline battery, instructions, protective lens shield, Long Form Certificate of Calibration traceable to NIST and two (2) year warranty.



Unique FLIP Display enables right-side-up viewing in any position



Conforms to: ISO 2178/2360/2808, prEN ISO 19840, ASTM B244/B499/B659/D1186/D1400/D7091/E376/G12, BS3900-C5, SSPC-PA2 and others.

© DeFelsko Corporation USA 2013. All Rights Reserved. Technical Data subject to change without notice. U.S. Patent # Re.35,703 • Printed in U.S.A. PDF.T.v.LW/W1303